

## GD-ML-CC2430HD

59.9 cm (23.6") LCD/TFT Monitor LED 16:9



- Designed for professional 24/7 usage
- Displays a full, flat 21,5" (54.6 cm) diagonal image
- LED Backpanel illumination
- Built-in Speaker
- 1 HDMI, 1 VGA Input



### ESSENTIAL

- Product Line ESSENTIAL: high quality, basic features and remarkably many functions for smaller applications

Item Code: GD-ML-CC2430HD

EAN CODE: 4260573063741

## Specifications GD-ML-CC2430HD

**Display**

LCD Panel size:	59.9 cm (23.6") Diagonal AM-TFT LED Backlight
Pixels - Total:	1920 (H) x 1080 (V)
Pixel Pitch:	0.248 mm (H) x 0.248 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

**Video**

Video Inputs:	1x HDMI, 1x VGA, 1x Audio
Video Standard:	PAL, NTSC
Brightness:	250 cd, m <sup>2</sup>
Contrast Ratio:	1000:1
Number of Colours:	16.7 million
Response Time:	5 ms

**General**

Speakers:	2 x 2 W
OSD (On Screen Display):	Yes, multi language
Accessories included:	Power Adapter and HDMI cable

**I/O Interface**

Audio Inputs:	1-ch, RCA (2.0 Vp-p, 1kΩ)
---------------	---------------------------

**Approvals**

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 50,000 hours

**Environmental**

Operating Temperature:	0 °C ~ +45 °C
Humidity:	Less than 90%, non condensing

**Electrical**

Supply Voltage:	12 VDC, Power Adapter 100 ~ 240 VAC 50, 60Hz included
Power Consumption:	Max. 25 W

**Mechanical**

Material:	Robust Plastic
Vesa Mount:	100 x 100 mm
Dimensions:	556 x 334 x 46 mm (21.9 x 13.2 x 1.8 inch)
Weight:	3230 g (7.12 lb)

## Dimensions:

Item Code: GD-ML-CC2430HD

EAN CODE: 4260573063741

