

HD-SDI Copper

GRUNDIG**1Ch HD-SDI to HDMI converter**

- HD-SDI to HDMI converter
- Full HD, 1920 x 1080p, 30/25 fps
- SMPTE 292/296M compliant

SUMMARY

Based on the Television Standard for FullHD Television, HD-SDI products feature up to 2 Megapixel (1920x1080) pictures in real-time (30fps) transmitted over coax cabling. Get the advantages of IP technology without their drawbacks. Get 16:9 megapixel pictures without network configuration, bandwidth problems and network security risks. Use existing coax cables and only exchange the cameras and recorders. Get a "real" live picture and see the things that happen in the now, not a few seconds ago. Connect a monitor directly to a camera using only a HD-SDI-to-HDMI converter. HD-SDI products are easy to handle, easy to install and produce amazing high quality pictures.

SPECIFICATIONS

Video Inputs	1 CH HD-SDI, BNC
Video Outputs	1 HDMI
Video Resolution	1080p 60RB, 1080p 60, 1080i 60, 720p 60
LED Indicator	Power, link
Compliant	SMPTE 274M/292M/296M
Operating Temperature	0°C ~ +50°C
Humidity	less than 80%, non condensing

HD-SDI Copper

GRUNDIG**SPECIFICATIONS**

Supply Voltage	12 VDC (External Power Supply)
Power Consumption	4 W
Weight	0.14 kg
Dimensions w*h*d	115 x 26x 65 mm

DIMENSIONS